NANO & TGS70

Manual positioners, 10 up to 70 Kg

BENCH POSITIONER with rotary table for manual welding of circular pieces. Load capacity: 10kg for NANO and 70 Kg for TGS70. Rotation activated by a direct current electrical motor, speed electronically adjusted. Pedal board and control module included in the supply. Manual working cycle 2T-4T.



HF shielding included in all the models

MODEL	NANO	TGS 70
Supply voltage 230V 1Ph	~	~
Weight Kg.	10	60
Table diameter mm.	160	350
Max. load Kg. (horizontal table and centred load)	10	70
Table orientation	0-180°	0-180°
Standard revolutions per minute speed (gear Ø 22)	0,5 - 12	0,3 - 5
Revolutions Per Minute speed (gear Ø 40 – included in standard supply)	×	0,6 - 10
Clearing hole Ø 20 mm	×	~
Electronic speed control	~	~
LEGENDA: ✓: Standard X: Not available		

NANO	Semiautomatic positioner, Pedal included	
TGS 70	Semiautomatic positioner, Pedal included	

TGS70 Options

2P	Double pedal for control of forward/backward motion	
EASY SPEED CONTROL	Pedal with speed control (not available with option 2P)	
OM 125	Self-centering chuck, diam. mm. 125	
OM 160	Self-centering chuck, diam. mm. 160	
OM 200	Self-centering chuck, diam. mm. 200	